



LPC system

metallic fittings for use with LPC conduits

- IP66
- IP67
- IP68
- IP69

Fittings

Multiflex Consulting Aps

Tel.: 5332 7083

C	C-S	C-90
<p>external metric thread nickel plated brass</p> <p>Multipart compression fitting including elastomeric seal. Can be used for knockout or threaded entries as fitting rotates until tightened.</p>	<p>swivel external thread nickel plated brass</p> <p>Multipart compression fitting including elastomeric seal. The external thread swivels about the main body even after tightening.</p> <p>Suitable for knockout or threaded entries.</p>	<p>90° external thread nickel plated brass</p> <p>90° multipart compression fitting including elastomeric seal. Can be used for knockouts.</p>
<ul style="list-style-type: none"> <li style="background-color: #76b82a; color: white; padding: 2px;">IP66 <li style="background-color: #76b82a; color: white; padding: 2px;">IP67 <li style="background-color: #76b82a; color: white; padding: 2px;">IP68 <li style="background-color: #76b82a; color: white; padding: 2px;">IP69 	<ul style="list-style-type: none"> <li style="background-color: #76b82a; color: white; padding: 2px;">IP66 <li style="background-color: #76b82a; color: white; padding: 2px;">IP67 <li style="background-color: #76b82a; color: white; padding: 2px;">IP68 <li style="background-color: #76b82a; color: white; padding: 2px;">IP69 	<ul style="list-style-type: none"> <li style="background-color: #76b82a; color: white; padding: 2px;">IP66 <li style="background-color: #76b82a; color: white; padding: 2px;">IP67 <li style="background-color: #76b82a; color: white; padding: 2px;">IP68 <li style="background-color: #76b82a; color: white; padding: 2px;">IP69



nominal size (mm)	LPC	for conduit see page 80			metric thread part number		
		metric thread part number	for PG thread size	for NPT thread size	thread	metric thread part number	metric thread part number
12	LPC12	LPC12-M16-C	LPC12-PG9-C			LPC12-M16-S	LPC12-M16-C90
16	LPC16	LPC16-M16-C	LPC16-PG11-C			LPC16-M16-S	LPC16-M16-C90
16	LPC16	LPC16-M20-C	LPC16-PG13-C	LPC16-050-C (1/2")		LPC16-M20-S	LPC16-M20-C90
20	LPC20	LPC20-M20-C	LPC20-PG16-C	LPC20-050-C (1/2")		LPC20-M20-S	LPC20-M20-C90
25	LPC25	LPC25-M25-C	LPC25-PG21-C	LPC25-075-C (3/4")		LPC25-M25-S	LPC25-M25-C90
32	LPC32	LPC32-M32-C	LPC32-PG29-C	LPC32-100-C (1")		LPC32-M32-S	LPC32-M32-C90
40	LPC40	LPC40-M40-C	LPC40-PG36-C	LPC40-125-C (1 1/4")		LPC40-M40-S	LPC40-M40-C90
50	LPC50	LPC50-M50-C	LPC50-PG42-C	LPC50-150-C (1 1/2")			LPC50-M50-C90
63	LPC63	LPC63-M63-C	LPC63-PG48-C	LPC63-200-C (2")			LPC63-M63-C90

* Please see conduit range information page 80

Ordering Notes

- * Indicates parts made to order on request and may be subject to MOQ and lead time
- **Available on request:**
 - additional sizes
 - alternative threads
 - alternative materials (eg. PU)

- other colours
- conduit couplers
- 45 degree brass elbow
- combined conduit fitting with cable gland, see page 124

Alternatives



see page 78