

# Liquid Tight Conduit fittings

## nickel plated brass fittings

IP66

IP67

IP68

IP69

## Fittings

Multiflex Consulting Aps

Tel: 5332 7083

| C   | C-S   | C-F  | C-SF   |
|---|---|--|--|
| <p><b>external thread nickel plated brass</b></p> <p>Multipart compression fitting including elastomeric seal. Can be used for knockout or threaded entries as fitting rotates until tightened.</p> | <p><b>swivel external thread nickel plated brass</b></p> <p>Compression fitting for knockout or threaded entries.</p> <p>Multipart compression fitting including elastomeric seal. The external thread swivels about the main body even after tightening.</p> | <p><b>internal thread nickel plated brass</b></p> <p>Multi part compression fitting including elastomeric seal to connect with an external thread.</p> | <p><b>swivel internal thread nickel plated brass</b></p> <p>Multi part compression fitting including elastomeric seal. Swivel internal thread makes it suitable for connection to male threads. Internal thread swivels about the main body even after tightening.</p> |
| IP66 IP67 IP68 IP69   | IP66 IP67 IP68 IP69   | IP66 IP67 IP68 IP69  | IP66 IP67 IP68 IP69  |



#



| nominal size (mm) | US trade size (") | outside dia (mm) | inside dia (mm) | metric thread part number | for PG thread size | for NPT thread size | metric thread part number | metric thread part number | metric thread part number |
|-------------------|-------------------|------------------|-----------------|---------------------------|--------------------|---------------------|---------------------------|---------------------------|---------------------------|
| 10                | ¼                 | 11.8             | 7.0             | LTP10-M12-C               | PG7                |                     |                           |                           |                           |
| 10                |                   |                  |                 | LTP10-M16-C               |                    |                     |                           |                           |                           |
| 12                | ⅝                 | 14.2             | 10.0            | LTP12-M16-C               | PG9                |                     | LTP12-M16-S               |                           |                           |
| 16                | ¾                 | 17.8             | 12.6            | LTP16-M16-C               | PG11               | 050 (½")            | LTP16-M16-S               |                           |                           |
| 16                |                   |                  |                 | LTP16-M20-C               | PG13               | 050 (½")            | LTP16-M20-S               |                           | LTP16-M20-SF              |
| 20                | ½                 | 21.1             | 16.0            | LTP20-M20-C               | PG16               | 050 (½")            | LTP20-M20-S               | LTP20-M20-F               | LTP20-M20-SF              |
| 25                | ¾                 | 26.4             | 21.0            | LTP25-M25-C               | PG21               | 075 (¾")            | LTP25-M25-S               | LTP25-M25-F               | LTP25-M25-SF              |
| 32                | 1                 | 33.1             | 26.5            | LTP32-M32-C               | PG29               | 100 (1")            | LTP32-M32-S               | LTP32-M32-F               |                           |
| 40                | 1¼                | 41.8             | 35.4            | LTP40-M40-C               | PG36               | 125 (1¼")           | LTP40-M40-S               | LTP40-M40-F               |                           |
| 50                | 1½                | 47.9             | 40.4            | LTP50-M50-C               | PG42               | 150 (1½")           | LTP50-M50-S               | LTP50-M50-F               |                           |
| 63                | 2                 | 59.7             | 51.6            | LTP63-M63-C               | PG48               | 200 (2")            |                           |                           |                           |

# When ordering PG or NPT please see below.

## Ordering Notes

- Add reel length eg: LTP20B-25M for a 25m reel
- For LTP specify colour (B = Black, G = Grey)
- \* Indicates parts made to order on request and may be subject to MOQ and lead time
- + Double interlock section

- **Available on request:**
  - longer lengths and bulk packaging
  - cut lengths and assemblies
  - C-S with PG threads
  - other colours
  - internal thread fittings

## How to read the fittings code

**Note:** For PG or NPT thread types please insert thread size listed to obtain part number

