



# Flexilok® system

IP66



## Construction: Nylon (PA66) moulded fitting.

- One piece fast fit
- Slim design
- IP rating: IP66
- Anti-vibration and tamper resistant
- Pull off strength with:  
(FLK21 - FPAS21 25kg)  
(FLK21 - FPAL21 20kg)
- Can be removed using a screwdriver
- Suitable for fine and coarse pitch conduits
- Temperature range -40°C to +120°C
- **Metric threads supplied complete with locknuts**
- Low Fire Hazard (LFH), see page 149
- Halogen, sulphur and phosphorus free
- Available in Black, Grey (RAL 7031) and white, see page 71
- 42mm and 54mm feature 4 teeth for added strength

## Fittings

Multiflex Consulting Aps  
tlf.: 5332 7083

			FLK	FLK	FLK-FLK
			straight external thread	Push in	coupler
			Nylon, one piece, slim, fast fit, external threaded fitting suitable for knockouts or threaded entries.	Simple, one piece, push in fitting suitable for knockouts with no need for locknuts. Ideal for use when enclosure access is restricted.	One piece, slim, fast fit coupler for joining 2 conduits together.
			IP66	IP66	IP66
					
			Ext Metric	Ext PG	Coupler
european (NW) sizes	nominal size (mm)	OD mm	FLK10-M12	FLK10-PG7	
			FLK13-M16	FLK13-PG9	
7	10	10.0			
7	10				
8	11	11.5			
10	13	13.0			
10	13				
10	13				
12	16	15.8	FLK16-M16	FLK16-PG11	FLK16-PL20
12	16		FLK16-M20	FLK16-PG13	FLK16-FLK16
12	16				
12	16				
14	18	18.5			
14	18				
	20	20.0	FLK20-M20		FLK20-PL20
17	21	21.2	FLK21-M20	FLK21-PG16	FLK21-PL20
17	21				FLK20-FLK20
17	21				FLK21-FLK21
	25	25.0	FLK25-M25		FLK25-PL25
23	28	28.5	FLK28-M25	FLK28-PG21	FLK28-PL25
23	28				FLK25-FLK25
					FLK28-FLK28
29	34	34.5	FLK34-M32	FLK34-PG29	FLK34-PL32
29	34				
					FLK34-FLK34
36	42	42.5	FLK42-M40	FLK42-PG36	
36	42		FLK42-M50		
48	54	54.5	FLK54-M50	FLK54-PG48	
48	54		FLK54-M63		
56	67	67.0			

## Ordering Notes

- Specify Black or Grey (B=Black, G=Grey) eg. FLK20-M20B
- For white version see page 71
- Details for removal tools can be found on page 131

## Also Available

- Push in fitting removal tool - see accessories page 131
- Brass threaded versions
- Two teeth version of 42mm and 54mm available on request

## Removal Tool



NOTE: 42mm and 54mm require a removal tool to aid removal if necessary see page 131.